



EUROCHEMICAL INDUSTRIES INC.LTD

Technical Data

## EUROBINDER 650

Area of application	<b>Eurobinder 650</b> emulsion of oils and resins.
Application	<b>Eurobinder 650</b> forms a very soft film which can be used in full grain finishing as basic component of polishable pregrounds. <b>Eurobinder 650</b> is used both alone and together with waxes, proteins or resins in the formulations of polishable pregrounds. It makes the absorption of the product more uniform by masking blind grain. It improves elasticity and it does not make darker the pregrounds grain colour. <b>Eurobinder 650</b> can be dyed both with anilines and pigments. It furthermore reduces the "wrinkling" defect which may occur with particularly hard finishings.
Physical form	Off – white viscous paste.
Characteristics	Composition: oil / resins Dry residue: 18 % approx. pH (1:10 with water): 7 – 8 approx.
Safety and Storage	Keep from freezing. Stir well before use and close recipients tightly after each withdrawal. Store between + 5 °C and + 40 °C When stored under these conditions, this product has a shelf life of at least six months.
Origin	European Community

All data and recommendations here in are accurate at the time of publication. Eurochemical Industries Inc. Ltd. reserves the right to modify them without notice. Work conditions and type of raw material can effect the final results. It is the responsibility of the user to apply the recommendations to the actual conditions and particular purpose.