



EUROCHEMICAL INDUSTRIES INC.LTD

Technical Data

EUROCRYL C 2002

Area of application	Eurocryl C 2002 compact binder for buffed upholstery.										
Application	Eurocryl C 2002 forms a tough, lightfast film of medium matt and softness, good coverage, low surface tack, excellent plate release and print retention both on the plate and on the rotary machine and very good dry / wet / alcohol rub – fastness.										
Physical form	Whitish milky liquid.										
Characteristics	<table> <tr> <td>Composition:</td> <td>Preparation based on acrylic co-polymers</td> </tr> <tr> <td>Dry residue:</td> <td>25 % approx.</td> </tr> <tr> <td>pH (1:10 with water):</td> <td>7.5 - 8.5 approx.</td> </tr> <tr> <td>NH₄OH Thickening:</td> <td>None</td> </tr> <tr> <td>Film features:</td> <td>Opalescent - smooth</td> </tr> </table>	Composition:	Preparation based on acrylic co-polymers	Dry residue:	25 % approx.	pH (1:10 with water):	7.5 - 8.5 approx.	NH ₄ OH Thickening:	None	Film features:	Opalescent - smooth
Composition:	Preparation based on acrylic co-polymers										
Dry residue:	25 % approx.										
pH (1:10 with water):	7.5 - 8.5 approx.										
NH ₄ OH Thickening:	None										
Film features:	Opalescent - smooth										
Safety and Storage	This product is not frost resistant. Store between +5° C and 40°C. If stored properly, this product is stable for at least twelve months.										
Origin	European Community										

All data and recommendations here in are accurate at the time of publication. Eurochemical Industries Inc. Ltd. reserves the right to modify them without notice. Work conditions and type of raw material can effect the final results. It is the responsibility of the user to apply and adjust the recommendations to the actual conditions and particular purposes.